

# RETHINK MONOPRINT

**M41,900.00**  
**Incl. VAT**



**RISO SF5030 E**

# RISO SF5030 E

<b>Master Making/Printing Methods</b>		High-speed digital master-making/Fully automatic printing
<b>Original Type</b>		Book or sheet
<b>Master Making Time*<sup>1</sup></b>	<b>Quick Master Making mode</b>	Approx. 20 seconds (A4, short-edge feed)
	<b>Normal Master Making mode</b>	Approx. 22 seconds (A4, short-edge feed)
<b>Resolution</b>	<b>Scanning</b>	600 dpi × 600 dpi
	<b>Printing</b>	300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
<b>Maximum Scanning Area</b>		297 mm × 432 mm
<b>Print Paper Weight</b>		46 gsm to 157 gsm
<b>Print Paper Size</b>		100 mm × 148 mm to 310 mm × 432 mm
<b>Maximum Printing Area</b>		210 mm × 290 mm
<b>Paper Feed Tray Stacking Capacity</b>		1000 sheets* <sup>2</sup> , stacking height of 110 mm or lower
<b>Paper Receiving Tray Stacking Capacity</b>		1000 sheets* <sup>2</sup> , stacking height of 110 mm or lower
<b>Print Speed</b>		5 levels: 60, 80, 100, 120 and 130 ppm
<b>Print Position Adjustment</b>		Horizontal: ±15 mm, Vertical: ±10 mm
<b>Image Processing Mode</b>		Line, Photo, Duo, Pencil
<b>Print Reproduction Ratio</b>		Zoom: (50% to 200%), 100% reduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%)
<b>User Interface</b>		LCD panel
<b>Functions</b>		Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto* <sup>3</sup> , Speed, Density, Print Position, Program A/B, D-feed check, Slip sheet sorting, Job Separation* <sup>4</sup> , Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Paper Memory Print, Auto Sleep Setting, Auto Power-OFF Setting, ECO mode, RISO iQuality System
<b>PC Interface</b>		USB2.0, Ethernet:100BASE-TX, 10BASE-T* <sup>5</sup>
<b>Ink Supply</b>		Full automatic (1000 ml/cartridge)
<b>Master Supply/Disposal</b>		Full automatic (A4: approx. 295 sheets per roll)/Disposal capacity: approx. 100 sheets
<b>Power Source</b>		AC 100-120 V 3.4 A, AC 220-240 V 1.6 A, 50-60 Hz
<b>Power Consumption</b>	<b>Standard</b>	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	<b>Optional Accessories Connected*<sup>6</sup></b>	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
<b>Dimensions (W×D×H)</b>	<b>In use</b>	1415 mm × 670 mm* <sup>7</sup> × 1065 mm* <sup>8</sup>
	<b>In storage</b>	780 mm × 670 mm* <sup>7</sup> × 1065 mm* <sup>8</sup>
<b>Required Space (W×D×H)</b>		1415 mm × 1240 mm × 1515 mm* <sup>8</sup>
<b>Weight</b>		100 kg* <sup>9</sup>

\*1 Measurement value when set to 100% reproduction ratio.

\*2 When using the following weight of paper: 64 gsm to 80 gsm

\*3 Usable when the optional auto document feeder is installed.

\*4 Usable when the optional Job Separator is installed.

\*5 RISO Network Kit S10 (optional) is required for connecting to the network.

\*6 When all the following optional accessories are installed, Auto Document Feeder, Job Separator, IC Card Reader.

\*7 The depth does not include the stabilizers for the dedicated stand.

\*8 The height includes the dedicated stand.

\*9 The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

## Optional Accessories



**RISO FII Type Drum**  
Enables color printing.  
(Case included)



**RISO Auto Document Feeder VII**  
Scans multiple documents automatically.



**RISO Job Separator IV; NIII**  
Enables easy separation of printed sheets by inserting tape strips.



**Card Feed Kit**  
Compatible with paper weight 100 gsm to 400 gsm.  
\*Please contact a RISO sales representative for the kinds of paper that may be used.



**RISO Stand D Type III**  
Deluxe and with doors for convenient storage with a neat appearance.



**RISO Stand N Type III**  
Sturdy open-front stand also offers convenient storage of consumables.

- **IC Card Reader Activation Kit RG**
- **RISO Network Kit S10**
- **RISO Printer driver for Macintosh**
- **Envelope Feed Kit**  
Compatible with paper weight 50 gsm to 120 gsm.

## RISO iQualitySystem™



The RISO iQuality mark indicates a RISO product compatible with the RISO iQuality System.



**RISO INK FII Type Color (1000 ml)**



**RISO MASTER FII Type (A4: 295 sheets)**



**RISO INK FII Type Black (1000 ml)**

# CV 3030

## NEW DESIGN COMPACT SIMPLE & STYLISH



**A4**  
**130 PPM**

HI-SPEED  
CERTIFIED **USB**  
USB Flash Print  
Large LCD Touch Panel

*Power Pedestal*

**M38,100.00**  
**Incl. VAT**



Keep printing, even when the power goes down!  
This solution is perfect for areas with sporadic power issues.  
This option allows the Risograph to run entirely independent of any  
mains connection. In this configuration, true off-the-grid printing is  
not only achievable, but simple to implement!

**RISO**



## Specifications:

Master-making/Printing Methods	High-speed digital master-making/fully automatic printing
Original Type	Sheet
Original Size (min./max.)	90 mm x 140 mm to 310 mm x 435 mm
Original Paper Weight	50 gsm to 107 gsm (13-lb bond to 29-lb bond)
Original Paper Capacity	Approx. 10 sheets (64 gsm to 80 gsm)/Maximum height 1 mm
Scanning Area (max.)	297 mm x 435 mm
Printing Paper Size (min./max.)	Minimum size: 100 mm x 148 mm (Maximum size: 257 mm x 364 mm)
Paper Supply Capacity	Approx. 1000 sheets (64 gsm to 80 gsm) Maximum height: 110 mm
Paper Receiving Capacity	Approx. 800 sheets (64 gsm to 80 gsm) Maximum height: 90 mm
Printing Paper Weight	50 gsm to 157 gsm
Image Processing Mode	Line, Photo, Duo, Pencil
Scanning Resolution	300 dpi x 600 dpi
Printing Image Resolution	300 dpi x 600 dpi (600 dpi x 600 dpi: Perforation density on the master)
Master-making Time	Approx. 35 seconds or less (for A4 originals/short edge feed/100% reproduction ratio)
Printing Area (max.)	In units of mm: 210 mm x 290 mm (when printing on legal size paper): 210 mm x 273 mm
Print Reproduction Ratio	In units of mm (100% reproduction ratio) Standard reproduction ratio (enlargement): 141%, 122%, 118%/Standard reproduction ratio (reduction): 94%, 87%, 82%, 71% In units of inches (100% reproduction ratio) Standard reproduction ratio (enlargement): 154%, 129%, 121%/Standard reproduction ratio (reduction): 94%, 78%, 65%, 61%
Print Speed	60 to 130 sheets per minute (five steps variable)
Print Position Adjustment	Vertical: ±10 mm Horizontal: ±10 mm
Ink Supply	Fully automatic (800 ml per cartridge)
Master Supply/Disposal	Fully automatic (235 sheets per roll)
Master Disposal Capacity	Approx. 30 sheets
User Interface	LCD panel
Computer Connection	USB PC Interface
Optional Accessories	Color Drum (Cylinder), Job Separator
Operating Noise	Max. 68 dB(A) (when printing 100 sheets per minute in the operator position)
Power Source*2	AC 100-120 V/220-240 V, 50-60 Hz <2.0 A/1.0 A>
Power Consumption	Max. 200 W/At Ready: 15 W or less/At Sleep: 10 W or less
Functions	Image Processing Mode (Line/Photo/Duo), Pencil, Enlargement/Reduction, Scanning Level, 2up, Auto Process, Proof, Print Position, Speed, Program (A/B), Confidential, Custom Setting Mode, Direct Printing, USB Flash-via-Printing, Consumables Information, Energy Saving Mode (Auto Sleep/Auto Power-OFF), RISO i Quality System
Dimensions	When in use: 1280 mm (W) x 655 mm (D) x 515 mm (H) When in storage: 665 mm (W) x 655 mm (D) x 505 mm (H)
Required Space	1280 mm (W) x 1255 mm (D) x 845 mm (H)
Weight*3	Approx. 65 kg
Safety Standards	IEC-60950-1 compliant, indoor, pollution degree 2*4, at altitudes of 2000 m or lower

Notes: • Please note that due to improvements and changes to the machine, some images and explanations in this leaflet may not correspond to your machine. • Specifications are subject to change without prior notice.

\*1 If the width of the paper surpasses 277 mm (10 29/32"), the horizontal print position adjustment width narrows depending on the width of the paper. \*2 To switch between 100-120 V and 220-240 V, contact your dealer (or authorized service representative). \*3 The weight does not include the ink and master. \*4 The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

### Value 1: Cost-efficient and time-saving

- Savings in print costs
- High-speed printing of 130 ppm

### Value 3: Excellent print quality

- High-quality printing at 300 dpi x 600 dpi
- Wide range of ink color variations
- Versatile paper handling capability

### Value 2: Convenient and easy operation


- Easy-to-operate LCD panel
- Convenient PC connectivity via USB
- Direct printing with a USB flash drive

### Value 4: Design that makes a difference

- Displays residual capacity of supplies
- Eco-friendly: Low power consumption, energy-saving system

### And more! New design

Intuitive operation



Compact, simple and stylish design



**M74,400.00  
Incl. VAT**



**Speed *F*orward**

**A new standard of performance that exceeds your expectations**

***SF5350***

A3/150 ppm/300 × 600 dpi/LCD panel/  
Versatile connectivity

## Optional Accessories



RISO SF Drum



RISO Auto Document Feeder VII



Job Separator IV; NIII



Card Feed Kit



RISO Key Card Counter IV; N



RISO Stand D Type III  
Deluxe and with doors for convenient storage with a neat appearance.



RISO Stand N Type III  
Sturdy open-front stand also offers convenient storage of consumables.

- IC Card Reader Activation Kit RG
- RISO Printer driver for Macintosh

## RISO iQualitySystem™



The RISO iQuality mark indicates a RISO product compatible with the RISO iQuality System.



RISO INK F Type Color (1000 ml)



RISO MASTER F Type  
(A3: 220 sheets)



RISO INK F Type (1000 ml)

## Specifications

<b>Master Making/Printing Methods</b>		High-speed digital master-making/Fully automatic printing
<b>Original Type</b>		Book or sheet
<b>Master Making Time<sup>*1</sup></b>	<b>Quick Master Making mode</b>	- Approx. 14 seconds (A4, long-edge feed) - Approx. 18 seconds (A4, short-edge feed)
	<b>Normal master making mode</b>	- Approx. 16 seconds (A4, long-edge feed) - Approx. 20 seconds (A4, short-edge feed)
<b>Resolution</b>	<b>Scanning</b>	600 dpi × 600 dpi
	<b>Printing</b>	300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
<b>Maximum Scanning Area</b>		297 mm × 432 mm
<b>Print Paper Weight</b>		46 gsm to 210 gsm
<b>Print Paper Size</b>		100 mm × 148 mm to 310 mm × 432 mm
<b>Maximum Printing Area</b>		291 mm × 413 mm
<b>Paper Feed Tray Stacking Capacity</b>		1000 sheets <sup>*2</sup> , stacking height of 110 mm or lower
<b>Paper Receiving Tray Stacking Capacity</b>		1000 sheets <sup>*2</sup> , stacking height of 110 mm or lower
<b>Print Speed</b>		6 levels: 60, 80, 100, 120, 130, and 150 ppm <sup>*3</sup>
<b>Print Position Adjustment</b>		Horizontal: ±15 mm, Vertical: ±10 mm
<b>Image Processing Mode</b>		Line, Photo, Duo, Pencil
<b>Print Reproduction Ratio</b>		Zoom: (50% to 200%), Free, 100% reduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%)
<b>User Interface</b>		LCD panel
<b>Functions</b>		Original Scanning mode, Scanning Level, Enlargement/Reproduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF-Semi-Auto <sup>*4</sup> , Speed, Density, Print Position, Program A/B, Job Separation <sup>*4</sup> , Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Auto Sleep Setting, Auto Power-OFFSetting, ECOmode, RISOiQuality System
<b>Ink Supply</b>		Full automatic (1000 ml/cartridge)
<b>Master Supply/Disposal</b>		Full automatic (A3: approx. 220 sheets per roll)/Disposal capacity: approx. 100 sheets
<b>Power Source</b>		AC 100-240 V, 50-60 Hz <3.4-1.6 A>
<b>Power Consumption</b>	<b>Standard</b>	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	<b>Optional Accessories Connected<sup>*5</sup></b>	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
<b>Dimensions (W×D×H)</b>	<b>In use</b>	1415 mm × 670 mm <sup>*6</sup> × 1065 mm <sup>*7</sup>
	<b>In storage</b>	780 mm × 670 mm <sup>*6</sup> × 1065 mm <sup>*7</sup>
<b>Required Space (W×D×H)</b>		1415 mm × 1240 mm × 1515 mm <sup>*7</sup>
<b>Weight</b>		101 kg <sup>*8</sup>
<b>Safety Information</b>		IEC-60950-1 compliant, indoor, pollution degree 2 <sup>*9</sup> , at altitudes of 2000 m or lower





[www.riso.co.za](http://www.riso.co.za)

# RETHINK MONOPRINT

**M85,600.00**  
**Incl. VAT**



**RISO SF9350E E**

# RISO SF9350 E

<b>Master Making/Printing Methods</b>		High-speed digital master-making/Fully automatic printing
<b>Original Type</b>		Book or sheet
<b>Master Making Time*<sup>1</sup></b>	<b>Quick Master Making mode</b>	- Approx. 14 seconds (A4, long-edge feed) - Approx. 18 seconds (A4, short-edge feed)
	<b>Normal Master Making mode</b>	- Approx. 16 seconds (A4, long-edge feed) - Approx. 20 seconds (A4, short-edge feed)
<b>Resolution</b>	<b>Scanning</b>	600 dpi × 600 dpi
	<b>Printing</b>	600 dpi × 600 dpi, Quick Master Making mode: 600 dpi × 400 dpi
<b>Maximum Scanning Area</b>		297 mm × 432 mm
<b>Print Paper Weight</b>		46 gsm to 210 gsm
<b>Print Paper Size*<sup>2</sup></b>		100 mm × 148 mm to 310 mm × 432 mm
<b>Maximum Printing Area</b>		291 mm × 413 mm
<b>Paper Feed Tray Stacking Capacity</b>		1000 sheets* <sup>3</sup> , stacking height of 110 mm or lower
<b>Paper Receiving Tray Stacking Capacity</b>		1000 sheets* <sup>3</sup> , stacking height of 110 mm or lower
<b>Print Speed</b>		6 levels: 60, 80, 100, 120, 130, and 150 (High Speed* <sup>4</sup> ) ppm
<b>Print Position Adjustment</b>		Horizontal: ±15 mm, Vertical: ±10 mm
<b>Image Processing Mode</b>		Line, Photo (Standard/Portrait), Duo (Standard/Line/Photo/Shadow off), Pencil (Darker/Lighter)
<b>Print Reproduction Ratio</b>		Zoom (50% to 200%), Free, 100% reproduction ratio, Margin+ (90% to 99 %), 4 levels of enlargement (163%, 141%, 122%, 116%), 4 levels of reduction (87%, 82%, 71%, 61%)
<b>User Interface</b>		Color touch panel
<b>Functions</b>		Image, Contrast, Size, Paper Size Detection, D-Feed Check, Dot Process, Contrast Adj., Tone Curve, Multi-Up Print, Book Shadow, Top Margin Adj., Binding Margin Adj., Max. Scan, Ink Saving, Quick Master Making, Preview, ADF Semi-Auto* <sup>5</sup> , Storage, Overlay, Print Speed Adj., Print Density Adj., Print Position Adj., Interval, Renew Page, Auto Page Renewal, Rotate, Special Paper Ctrl, Program, Slip Sheet Sorting, Job Separation* <sup>6</sup> , Job Memory, Reservation, Editor, Idling Action, Confidential, My Direct Access, Meter Display, ID Counter Report, Proof Copy, Direct Printing, USB Job List, Paper Memory Print, Scanning Mode, Admin., Auto Sleep, Auto Power-OFF, Power-OFF Schedule, ECO Mode, Protect, RISO iQuality System
<b>PC Interface</b>		USB2.0, Ethernet:100BASE-TX, 10BASE-T
<b>Ink Supply</b>		Full automatic (1000 ml/cartridge)
<b>Master Supply/Disposal</b>		Full automatic (A3: approx. 220 sheets per roll)/Disposal capacity: approx. 100 sheets
<b>Power Source</b>		AC 100-240 V, 50-60 Hz <3.4-1.6 A>
<b>Power Consumption</b>	<b>Standard</b>	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	<b>Optional Accessories Connected*<sup>7</sup></b>	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
<b>Dimensions (W×D×H)</b>	<b>In use</b>	1415 mm × 670 mm* <sup>8</sup> × 1065 mm* <sup>9</sup>
	<b>In storage</b>	780 mm × 670 mm* <sup>8</sup> × 1065 mm* <sup>9</sup>
<b>Required Space (W×D×H)</b>		1415 mm × 1240 mm × 1515 mm* <sup>9</sup>
<b>Weight</b>		102 kg* <sup>10</sup>

\*1 Measurement value when set to 100% reproduction ratio.

\*2 When the optional Wide Stacking Tray is installed, you can use paper up to a size of 310 mm × 555 mm by setting [Custom Paper Entry].

Depending on the paper type and paper size, papers may not be aligned properly.

\*3 When using the following weight of paper; 64 gsm to 80 gsm

\*4 If the temperature of the inside of the print drum (cylinder) is less than 5°C, [High Speed] is not usable.

\*5 Usable when the optional auto document feeder is installed.

\*6 Usable when the optional Job Separator is installed.

\*7 When all the following optional accessories are installed; Auto Document Feeder, Job Separator, IC Card Reader.


\*8 The depth does not include the stabilizers for the dedicated stand.

\*9 The height includes the dedicated stand.

\*10 The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

## Optional Accessories



**RISO FII Type Drum**  
Enables color printing.  
(Case included)



**RISO Auto Document Feeder AF-VII**  
Scans multiple documents automatically.



**RISO Job Separator IV, NIII**  
Enables easy separation of printed sheets by inserting tape strips.



**Card Feed Kit**  
Compatible with paper weight 100 gsm to 400 gsm.  
\*Please contact a RISO sales representative for the kinds of paper that may be used.



**Wide Stacking Tray**  
Allows use of paper up to 555 mm on the long edge.



**RISO Stand D Type III**  
Deluxe and with doors for convenient storage with a neat appearance.



**RISO Stand N Type III**  
Sturdy open-front stand also offers convenient storage of consumables.

- IC Card Reader Activation Kit RG
- RISO Printer driver for Macintosh
- Envelope Feed Kit  
Compatible with paper weight 50 gsm to 120 gsm.

## RISO iQualitySystem™



The RISO i Quality mark indicates a RISO product compatible with the RISO i Quality System.



**RISO INK FII Type Color (1000 ml)**



**RISO MASTER FII Type (A3: 220 sheets)**



**RISO INK FII Type Black (1000 ml)**